

By browsing our site you agree to our use of cookies.
If not please press the back button and clear cookies.

People need trees, trees need people...



[Download Arbortech PDF Brochure](#)

[Print this page](#)

Tel: 01225 837 109 M: 07971 000 964

[About Arbortech](#)

[Arbortech Products](#)

[Environmental Policy](#)

[Planting Projects - Hampton Court](#)

[Planting Projects - Hackney](#)

[Contact Arbortech](#)

Tree Watering / Root Drencher - Patent applied for

[Download page as PDF](#)

The Arbortech Root Drencher:

- Guarantees application of water to exactly where it is needed – the root ball.
- Is a fraction of the cost of limited capacity underground irrigation systems and can cut tree watering time and cost by up to 60%.
- Root Drencher demonstrates to the public a commitment to effective tree welfare
- One simple 30 second visit by tree watering personnel is all that is needed to ensure the application of 18-20 Litres of water directly to the root ball over a 1 to 2 hour period.

Please see the [Hampton Court Palace project](#) which utilised 500 Root Drencher units with 100% tree survival.



Thousands of Root Drencher Tree Watering units have been used on extensive planting projects throughout the UK with excellent feedback from satisfied clients.

Root Drencher should ideally be installed at the time of tree planting.



Simply open up the unit from it's flat pack form and close off the base by folding the tabs over.



Before completely filling in the tree planting pit rest the Root Drencher firmly in contact with the top of the tree root ball with the back of the unit resting against the tree support post.



When used as part of the Arbortech system, the Arbortech Tree Restraint distances the Root Ball from the support post, Root Drencher can then be positioned between the post and the tree

Before closing off the top of the Root Drencher drop a couple of shovels of soil into the unit to help facilitate a partial water seal at the base, (at this time a handful of slow release fertilizer can be introduced if required).



Close the top of the unit off and secure to the fixing post using a single screw or nail, (see illustration opposite). Ensure that the Root Drencher base remains in firm contact with the top of the root ball.



Finish filling in the tree planting pit thus partially burying the Root Drencher base.



2 years on and photographed in September 08, this planting in Hackney has flourished with the tree putting on 100% girth growth (the tree restraint can now be removed). The watering period during drought periods is one application of 30 litres every 10 days to 2 weeks. This is achieved by simply filling the Arbortech Root Drencher to overflowing and then moving to the next tree.

TREE WATERING / ROOT DRENCHER

Quantity	Discount	Unit Price
1-49	0%	£17.45
50 - 99	5%	£16.10
100 - 499	10%	£15.71
500 +	15%	£14.83

Weight 20 units packed - 14.0 Kg



- PROPORTION OF PRODUCT CAN BE RECYCLED AFTER USE - 100%
- REUSE OF PRODUCT? Yes
- PROPORTION OF RECYCLED MATERIAL USED IN MANUFACTURE OF PRODUCT 100%
- QUALITY ASSURED & CERTIFIED POLYMER COATING FOR MAXIMUM REUSE - Yes
- SUBTERRANEAN COMPONENTS BIO-DEGRADABLE - N/A



Arbotech products are made in the UK



Arbotech designs are IPO registered



[Home](#) | [Products](#) | [Environmental](#) | [Contact Arbortech](#) | [Download Arbortech brochure](#)